



Carbonair's gas phase carbon absorbers are designed to provide an efficient and economical means to control odor, toxic vapors, and corrosive gases. Several types of activated carbons are available for a variety of applications.

Specifications*



Model	GPC 3	GPC 3H	GPC 3.85
Flow Range (cfm)	20 - 100	20 - 270	36 - 360
Carbon Capacity (lb)	200	180	250
Vessel Diameter or Plot Size	2'	2'	2'-4"
Vessel Height	3'-0"	3'-0"	3'-6"
Bed Area (ft ²)	2.7	2.7	3.7
Empty Weight (lb)	65	65	100
Operating Weight (lb)	265	265	350
Influent Connection	2" FPT	4" FPT	4" FPT
Effluent Connection	2" FPT	4" FPT	4" FPT

Design Features

- Drums meet UN standards
- Baked enamel exterior
- Epoxy-phenolic interior lining

Options

- Influent/effluent sample and pressure taps
- Influent/effluent ducting
- Humidity control
- Discharge stack
- Blowers
- Complete line of granular activated carbon

Service Centers

FLORIDA
4710 Dignan Street
Jacksonville, FL 32254
800.241.7833
904.387.4465
904.387.5058 Fax

MINNESOTA
7500 Boone Ave N #101
Brooklyn Park, MN 55428
800.526.4999
763.315.4771
763.315.4614 Fax

TEXAS
4889 Hunter Rd. Bldg 1-C
San Marcos, TX 78666
800.893.5937
512.392.0085
512.392.0066 Fax

VIRGINIA
4003 West Main Street
Salem, VA 24153
800.204.0324
540.380.5913
540.380.5920 Fax

*Specifications subject to change without notice.

Dwg # 217357 Drum